

# MATERIAL SAFETY DATA SHEET

270-XXXXX ALL AEROSOL COLORS

Date Printed: 5/24/2013

Page 1 of 4

**PRODUCT NAME:** 270-XXXXX ALL AEROSOL COLORS  
**FORMULA KEY:** FAS-270-XXXXAER

**HMIS CODES:** H F R P  
2 3 0 I

===== SECTION I - MANUFACTURER IDENTIFICATION =====

**MANUFACTURER'S NAME:** Custom Paint USA  
**ADDRESS** : 3735 E. University Dr.  
McKinney, Tx 75069

**EMERGENCY PHONE** : 1-800-535-5053 **DATE PRINTED** : 5/24/2013  
**INFORMATION PHONE** : 1-972-542-6585 **NAME OF PREPARER** : Chris Crider

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg	@ TEMP	PERCENT
ACETONE	67-64-1	181.7	20 C	32.30
OSHA PEL: 750 PPM				
ACGIH TLV: 500 PPM				
PROPANE	74-98-6	110	70 F	13.20
OSHA PEL: 1000 PPM				
ACGIH TLV: 1000 PPM				
* XYLOL	1330-20-7	8	68 DEG F	11.05
OSHA PEL/TWA IS 100PPM				
ACGIH TLV/TWA IS 100 PPM				
ACGIH TLV/STEL IS 100 PPM				
NORMAL BUTANE	106-97-8	17	70 F	6.20
OSHA PEL: 800 PPM				
ACGIH TLV: 800 PPM				
1-METHOXY 2-PROPYL ACETATE	108-65-6	4.9	20 DEG C	3.65
ACGIH (THV) : NOT ESTABLISHED				
ONTARIO : 50 PPM TWA				
SOLVENT NAPHTHA	8032-32-4	26	100 F	2.75
OSHA PEL/TWA: 300 ppm				
ACGIH TLV/TWA 300 ppm				
N-BUTYL ACETATE	123-86-4	10	68 DEG F	1.70
OSHA PEL: 150 PPM				
ACGIH TLV: 150 PPM				
* EB ETHYLENE GLYCOL BUTYL ETHER	111-76-2	88	25 DEG C	1.20
OSHA PEL: 50 PPM      HAP's - NO				
ACGIH: 20PPM				
* TOLUOL	108-88-3	24	20 DEG C	1.10
OSHA PEL= 200 PPM				
ACGIH PEL= 100 PPM				
GLYCOL ETHER PM	107-98-2	88	25 DEG C	.60
OSHA PEL: 50 PPM				
METHYL N-AMYL KETONE	110-43-0	2.1	68 DEG F	.55
OSHA PEL: 100 PPM				
ACGIH: 100 PPM				
## BLACK	1333-86-4	3	68 F	.45
BLACK PIGMENT IS A SOLID NOT A LIQUID.				
OSHA PEL 3.5mg/m3				
ACGIH TLV 3.5mg/m3				
* ## ETHYL BENZENE	100-41-4	7.1	20 DEG C	.45
OSHA PEL: 100 PPM				



# MATERIAL SAFETY DATA SHEET

270-XXXXX ALL AEROSOL COLORS

Date Printed: 5/24/2013

Page 3 of 4

## SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

May cause moderate skin irritation. May be harmful if absorbed through the skin. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

## INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Harmful or fatal if swallowed.

## HEALTH HAZARDS (ACUTE AND CHRONIC):

Avoid long term and repeated contact.

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Not applicable.

## EMERGENCY AND FIRST AID PROCEDURES:

INGESTION: If swallowed, do not induce vomiting. EYES: In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes. SKIN: Wash effected area throughly with soap and water. INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Provide maximum ventilation. Only personnel equipped with proper respiratory and skin and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sawdust, vermiculite, or other absorbent material and place into containers for disposal.

### WASTE DISPOSAL METHOD:

Waste material must be disposed of in accordance with Federal, State, and Local environmental control regulations. Empty containers should be recycled or disposed of through an approved Waste Management Facility.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Do not store above 120 deg. F. Store large quantities in buildings designed and protected for storage of NFPA Flammable liquids.

### OTHER PRECAUTIONS:

If this material is part of a multiple component coating system, read the MSDS for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inchs. Containers of this material may be hazardous when emptied since they retain residues. Do not cut, puncture, or weld on or near container.

## ===== SECTION VIII - CONTROL MEASURES =====

### RESPIRATORY PROTECTION:

Overexposure to vapors may be prevented by ensuring ventilation controls, vapor exhaust or fresh air entry. If TLV of any component is exceeded, use an appropriate NIOSH/MSHA approved respirator. Follow respirator manufacturers directions for respirator use.

### VENTILATION:

Provide sufficient general exhaust or local exhaust (preferred) ventilation to keep the concentration of ingredients listed in Section II below the lowest exposure limits.

### PROTECTIVE GLOVES:

Impermeable chemical handling gloves for skin protection.

### EYE PROTECTION:

Wear safety glasses with unperforated side shields.

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

# MATERIAL SAFETY DATA SHEET

270-XXXXX ALL AEROSOL COLORS

Date Printed: 5/24/2013

Page 4 of 4

Personal protective equipment for the body should be selected based on the task being performed and the risks involved.

## WORK/HYGIENIC PRACTICES:

Eye washes and safety showers in the workplace are recommended.

## ===== SECTION IX - TRANSPORTATION INFORMATION =====

PROPER SHIPPING NAME	HAZARD CLASS	UN NUMBER	PACKING GROUP
AEROSOLS, FLAMMABLE	2.1	UN1950	

## ===== SECTION X - DISCLAIMER =====

The information and recommendations contained herein are believed to be accurate at the time of preparation or obtained from sources believed to be generally reliable. Fasse Paint Co. will not be held liable for claims relating to any party's use of or reliance on information contained herein, regardless of whether it is claimed the information is inaccurate.