

# Safety Data Sheet

# Painted TruZinc<sup>®</sup> Steel, Rawhide, Steelscape Prints<sup>®</sup>, TruzGuard<sup>®</sup>, Vintage<sup>®</sup>, Vintage<sup>®</sup> Heritage

### Section 1 - Chemical Product and Company Identification

Product name	Painted TruZinc <sup>®</sup> Steel, Rawhide, Steelscape Prints <sup>®</sup> , TruzGuard <sup>®</sup> , Vintage <sup>®</sup> , Vintage <sup>®</sup> Heritage
Manufacturer	Steelscape, LLC 222 West Kalama River Road Kalama, WA 98625
Revision Date	11/02/2020
Reference No.	2000000009
Emergency Contact:	CHEMTREC (24 hours) 1-800-424-9300

### Section 2 - Hazards Identification

### **GHS Label Elements:**

**Hazard Pictograms:** 



#### Signal Word:

Warning

### Hazard Statement:

Does not pose a health hazard in its normal form. Inhalation of metal dust and fume may result from further processing by the user, particularly during welding, burning, grinding and machining activities. These potential health hazards should be evaluated by the user. A non-metallic passivation treatment is normally applied based upon customer/end use criteria. These non-metallic coatings may contain hazardous substances of varying amounts. During processing, substances of varying chemical composition and quantity may be generated by the surface passivant. SDS information regarding the surface passivant shall be supplied to the user upon request.

#### Carcinogenity:

Certain chromium and nickel compounds as well as organic compounds found in various coating materials have been listed as carcinogens by the NTP, IARC, or OSHA.

#### Medical Conditions Aggravated by Long Term Exposure:

Individuals with chronic respiratory disorders (i.e., asthma, chronic bronchitis, emphysema, etc.) may be adversely affected by any fume or airborne particulate matter exposure.

#### **Chronic Effects:**

Chronic inhalation concentrations of iron oxide fumes or dusts may lead to a benign pneumoconiosis (siderosis). Inhalation of high concentrations of ferric oxide may possibly enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens. Chronic inhalation concentrations of aluminum fumes or dusts may lead to a fibrotic lung condition known as Shaver's disease; however, evidence for this is not conclusive since affected workers were exposed to other substances (silica) as well. The inhalation of high concentrations of dust from manganese, copper, lead and/or zinc in the respirable particle size range can cause an influenzalike illness termed metal fume fever. Typical symptoms last 12 to 48 hours and are characterized by metallic taste in mouth, dryness and irritation of the throat, followed by weakness, muscle pain, fever and chills. Continuous exposures to high concentrations of manganese can cause central nervous system disorders and manganese pneumonia. Fibrosis of lung tissue from manganese exposure has also been reported for products containing manganese only. Overexposure to aluminum dust can cause shortness of breath. Long term inhalation exposure to high concentrations (overexposure) to pneumoconiotic agents may act synergistically with inhalation of oxides, fumes or dusts of this product to cause toxic effects. Prolonged or repeated contact with unprotected skin may result in skin irritation. Torching or burning operations on steel products with oil or organic coating may produce emissions which can be irritating to the eyes and respiratory tract.

### **Precautionary Statement:**

Inhalation of metal dust and fume may result from further processing by the user, particularly during welding, burning, grinding and machining activities. These potential health hazards should be evaluated by the user.

	CAS-No.	Weight%	
Ingredient Name		Min	Max
Base Metal			
Iron	7439-89-6	Balance	99.00
Carbon	7440-44-0		0.30
Manganese Compounds (as Mn)	7439-96-5		1.2
Phosphorus	7723-14-0		0.15
Sulfur	7704-34-9		0.05
Silicon	7440-21-3		0.05
Aluminum	7429-90-5		0.10
Note: Base Steel may contain the following trace or resi Molybdenum (0.10% max), Nickel (0.12% max), Columb Vanadium (0.08% max).			
Molybdenum (0.10% max), Nickel (0.12% max), Columb			
Molybdenum (0.10% max), Nickel (0.12% max), Columb Vanadium (0.08% max). Metallic Coating Aluminum	bium (0.06% max), Tin (0.03%	6 max), Titanium (0.06	6% max), and
Molybdenum (0.10% max), Nickel (0.12% max), Columb Vanadium (0.08% max). Metallic Coating	bium (0.06% max), Tin (0.03%	6 max), Titanium (0.06	6% max), and
Molybdenum (0.10% max), Nickel (0.12% max), Columb Vanadium (0.08% max). Metallic Coating Aluminum Zinc (Reportable as a fume or dust) Iron	bium (0.06% max), Tin (0.03% 7429-90-5 7440-66-6	6 max), Titanium (0.06	6% max), and 0.5 48.00
Molybdenum (0.10% max), Nickel (0.12% max), Columb Vanadium (0.08% max). Metallic Coating Aluminum Zinc (Reportable as a fume or dust)	bium (0.06% max), Tin (0.03% 7429-90-5 7440-66-6	6 max), Titanium (0.06	6% max), and 0.5 48.00 0.02
Molybdenum (0.10% max), Nickel (0.12% max), Columb Vanadium (0.08% max). Metallic Coating Aluminum Zinc (Reportable as a fume or dust) Iron Surface Coating	bium (0.06% max), Tin (0.03% 7429-90-5 7440-66-6	6 max), Titanium (0.06	6% max), and 0.5 48.00 0.02
Molybdenum (0.10% max), Nickel (0.12% max), Columb Vanadium (0.08% max). Metallic Coating Aluminum Zinc (Reportable as a fume or dust) Iron Surface Coating Polyester, siliconized polyester, alkyd, fluorocarbon(PVDF),epoxy, urethane, latex or acrylic paints and primers	bium (0.06% max), Tin (0.03% 7429-90-5 7440-66-6	6 max), Titanium (0.06	6% max), and 0.5 48.00 0.02
Molybdenum (0.10% max), Nickel (0.12% max), Columb Vanadium (0.08% max). Metallic Coating Aluminum Zinc (Reportable as a fume or dust) Iron Surface Coating Polyester, siliconized polyester, alkyd, fluorocarbon(PVDF),epoxy, urethane,	bium (0.06% max), Tin (0.03% 7429-90-5 7440-66-6	6 max), Titanium (0.06	6% max), and 0.5 48.00 0.02 0.01
Molybdenum (0.10% max), Nickel (0.12% max), Columb Vanadium (0.08% max). Metallic Coating Aluminum Zinc (Reportable as a fume or dust) Iron Surface Coating Polyester, siliconized polyester, alkyd, fluorocarbon(PVDF),epoxy, urethane, latex or acrylic paints and primers	bium (0.06% max), Tin (0.03% 7429-90-5 7440-66-6 7439-89-6	6 max), Titanium (0.06	6% max), and 0.5 48.00

### Section 3 - Composition / Information on Ingredients

### Section 4 - First Aid Measures

### Eye contact:

Treat any foreign body in eye by flushing with large amounts of water. Seek medical attention immediately.

### Skin contact:

Skin hazards are not expected. However, should dermatitis develop, affected area should be washed with mild soap and water. If irritation or other symptoms develop, seek medical attention. Precautions should be taken to protect against sharp steel edges. If the skin is abraded by handling, seek medical attention.

### Ingestion:

Ingestion hazards are not expected.

#### Inhalation:

For treatment of overexposure to fumes and/or particulates, remove exposed individual to fresh air and seek medical attention. Administer artificial respiration or oxygen if breathing is difficult or has stopped.

## Section 5 - Fire-Fighting Measures

Not flammable or combustible. Steel products in the solid state present no fire or explosion hazard and do not contribute to the combustion of other materials.

## Section 6 - Accidental Release Measures

Not applicable to this metal in its solid state. For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust. Fine, dry material should be removed by vacuuming or wet sweeping methods to prevent spreading of dust. Avoid using compressed air. Do not release into sewers or waterways. Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations.

## Section 7 - Handling and Storage

Operations with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. Practice good housekeeping. Avoid breathing fumes and/or dust.

### Section 8 - Exposure Controls / Personal Protection

### **Respiratory protection:**

NIOSH/MSHA approved dust and fume respirators should be used to avoid excessive inhalation of particulates. Appropriate respirator selection depends on the magnitude of exposure.

### Hand protection:

Protective gloves should be worn as required for welding, burning or handling operations. If material is supplied with oil or other organic coating, wear protective gloves. However, do not continue to use gloves or work clothing that have become saturated with oil. Wash hands and any additional contact areas with soap and water or waterless hand cleaner.

### Eye protection:

Use safety glasses or goggles as required for welding, burning, sawing, brazing, grinding or machining operations.

### Engineering measures:

Local exhaust ventilation should be provided when welding, burning, sawing, brazing, grinding or machining to prevent excessive dust or fume exposure.

### Personal protection equipment:

Operations with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. Avoid breathing fumes and/or dust.

### Section 9 - Physical and Chemical Properties

#### Physical State: Solid

Appearance: Thin sheet metal color, varies w/ topcoat used. Odor: None Vapor Pressure (mm Hg): N/A Vapor Density (air = 1): N/A Formula Weight: N/A Density: N/A Sp. Gravity(H2O = 1): 7.8000N/A pH: N/A Water Solubility: Insoluble Other Solubilities: N/A Boiling point/range: N/A Freezing/Melting Point: N/A Viscosity: N/A Refractive Index: N/A Surface Tension: N/A % Volatile: N/A Evaporation Rate: N/A

### Section 10 - Stability and Reactivity

### **Chemical Stabilibity:**

Stable under normal conditions of use, storage and transport.

### Hazardous Conditions to Avoid:

Will react with strong acid to liberate hydrogen. Finely divided material may react with water, strong oxidizers, alkaline, and hydrogenated compounds. At temperatures exceeding the melting point of the metallic coating, fumes may be liberated which contain oxides of the metallic coating constituents. At temperatures exceeding the melting point of the base metal, fumes may be liberated which contain oxides of iron and other steel alloying elements.

Section 11 - Toxicological	Information
----------------------------	-------------

Ingredient Name	LD50 or LC50 Species /Route	OSHA PEL	ACGIH TLV(mg/m3) (TWA unless specified)
Base Metal			
Iron	mouse/oral 5.4 mg/kg	10 Iron Oxide Fume	5 Iron Oxide Fume as Fe
Carbon	No Information	Not Established	Not Established
Manganese Compounds (as Mn)	rat/oral 9 mg/kg	5 ceiling as Mn	5 Dust as Mn 1 Fume as Mn 3 Fume as Mn (STEL)
Phosphorus	No Information	.1 Total	Not Established
Sulfur	No Information	15 Total Dust	13 as SO2
Silicon	No Information	15 Total Dust 5 Respirable Fraction	10 Total
Aluminum	No Information	10 Total Dust 5 Respirable Fraction	10 Metal Dust as Al
Metallic Coating			
Aluminum	No Information	10 Total Dust 5 Respirable Fraction	10 Metal Dust as Al
Zinc (Reportable as a fume or dust)	No Information	5 Fume as ZnO	5 Fume as ZnO
Iron	mouse/oral 5.4 mg/kg	10 Iron Oxide Fume	5 Iron Oxide Fume as Fe
Surface Coating			
Polyester, siliconized polyester, alkyd, fluorocarbon(PVDF),e poxy, urethane, latex or acrylic paints and primers	No Information	Not Established	Not Established
Polyvinyl Chloride	No Information		
Polyethylene film	No Information	Not Established	Not Established
Strontium Chromate- 7789-06-2	No Information	Not Established	Not Established

# Section 12 - Ecological Information

No data available for product as a whole. However, individual components have been found to be toxic to the environment. Metal dusts may migrate into soil and groundwater and be ingested by wildlife. Lead can be bioaccumulated in plants and water organisms, especially shellfish.

# Section 13 - Disposal Consideration

Scrap should be recycled whenever possible. Product dusts and fumes from processing operations should also be recycled, or classified by a competent environmental professional and disposed of in accordance with applicable federal, state or local regulations.

# Section 14 - Transport Information

Not listed as a hazardous substance under 49 CFR 172.101.

# Section 15 - Regulatory Information

SARA 311/312 Codes (40CFR370): Immediate (acute) health hazard and delayed (chronic) health hazard. SARA 313 (40CFR372.65): Manganese and Lead are subject to SARA 313 reporting

requirements. Please note that if you prepackage or redistribute this product to industrial customers, SARA 313 requires that a notice be sent to those customers.

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): The product as a whole is not listed. However, individual components of the product are listed. OSHA Specifically Regulated Substance: Lead (29 CFR 1910.1025).

### Section 16 - Other Information

#### **Proposition 65 Statement:**

WARNING: This product may contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

This Safety Data Sheet (SDS) has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the Supplier Notification Requirements of SARA Title III, Section 313. This SDS represents products which may contain toxic chemicals.

The information contained in this SDS was obtained from sources which are believed to be reliable by the manufacturer. However, the information is provided without any responsibility or warranty, expressed or implied regarding its accuracy or correctness. The conditions or methods of handling, storage, use and disposal of this product are beyond the knowledge of the manufacturer. For this and other reasons, the manufacturer does not assume responsibility and expressly disclaims liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.